

FOUR WHEEL SERIES

420X4

MODEL	420X4
Capacity*	3.7 GPM
Pressure*	2000 PSI
Pump	Triplex, Oil Bath, Belt Drive
Motor/Voltage**	5 HP, 230 V, 1 PH, Fuse for 30 Amp.
Coil (Steel Pipe) Cold Water Wrap, Spiral Heating Section	126', Schedule 80
Burner, Pressure Atomizing, Auto Ignition, Fuel Consumption	Kero, or #1 Diesel, 350,000 BTU, 2.50 GPH
Fuel Tank	Plastic, 8 Gal.
Stack Size	8"
Temp. Control	Optional
Chemical	Precise Metered
Float Tank	Stainless Steel
Steam Capacity (Optional)	120 GPH
Dimensions	L - 46" W - 31" H - 49"
Shipping Weight	545 lbs.



Note: All 115 volt units have ground fault interrupters standard.
 *Gallonages and pressure may vary - + 5% due to manufacturing tolerances in components.
 **Special voltages on request. Gallonages and pressure may be less on 3 phase current.
 Also available ETL certified to UL 1776 standards and CSA-B140.11-M89.



Express Pressure Washers Inc.

526 3rd St NE

Blooming Prairie, MN 55917

PH: (507) 583-2703

www.expresspressurewashers.com