

# GAS FIRED SERIES

## 5181

<b>MODEL</b>	<b>5181*</b>
<b>Capacity**</b>	5 GPM
<b>Pressure**</b>	1800 PSI
<b>Pump</b>	Triplex, Oil Bath
<b>Motor***</b>	6 HP, 208/230 V, 1 or 3 PH
<b>Coil**** (Steel Pipe)</b>	243', 1/2" ID Schedule 80
<b>Burner Natural, Aspirating Natural</b>	440,000 BTU
<b>Gas Consumption</b>	NG-420 Cu. Ft. Per Hr. LP-5.4 GPH
<b>Stack Size</b>	12"
<b>Temp. Control</b>	Optional
<b>Chemical</b>	Precise Metered
<b>Float Tank Stainless Steel</b>	Standard
<b>Steam Capacity (Optional)</b>	150 GPH
<b>Dimensions</b>	L-55" H-54" W-25 1/2"
<b>Shipping Weight</b>	840 lbs.



Note: All 115 volt units have ground fault interrupters standard.  
 \*Gallonages and pressure may vary - + 5% due to manufacturing tolerances in components.  
 \*\*Special voltages on request. Gallonages and pressure may be less on 3 phase current.  
 Also available ETL certified to UL 1776 standards and CSA-B140.11-M89.



**Express Pressure Washers Inc.**

526 3rd St NE

Blooming Prairie, MN 55917

PH: (507) 583-2703

[www.expresspressurewashers.com](http://www.expresspressurewashers.com)