

FOUR WHEEL SERIES

518X4

MODEL	518X4
Capacity*	4.8 GPM
Pressure*	1800 PSI
Pump	Triplex, Oil Bath, Belt Drive
Motor/Voltage**	6 HP, 230 V, 1 PH, Fuse for 30 Amp.
Coil (Steel Pipe) Cold Water Wrap, Spiral Heating Section	158', Schedule 40
Burner, Pressure Atomizing, Auto Ignition, Fuel Consumption	Kero, or #1 Diesel, 540,000 BTU, 3.85 GPH
Fuel Tank	Plastic, 8 Gal.
Stack Size	8"
Temp. Control	Optional
Chemical	Precise Metered
Float Tank	Stainless Steel
Steam Capacity (Optional)	150 GPH
Dimensions	L - 54" W - 32" H - 49"
Shipping Weight	665 lbs.



Note: All 115 volt units have ground fault interrupters standard.
 *Gallonages and pressure may vary - + 5% due to manufacturing tolerances in components.
 **Special voltages on request. Gallonages and pressure may be less on 3 phase current.
 Also available ETL certified to UL 1776 standards and CSA-B140.11-M89.



Express Pressure Washers Inc.

526 3rd St NE

Blooming Prairie, MN 55917

PH: (507) 583-2703

www.expresspressurewashers.com