



**QUIET  
LOW RPM  
QUALITY**

### PRODUCT NUMBERING SYSTEM

# A050V060-1230

#### HORSEPOWER

**050:** 5 HP

#### TANK ORIENTATION

**V:** Vertical  
**H:** Horizontal

#### TANK SIZE

**060:** 60 Gal

#### PHASE

**1:** Single  
**3:** Three

#### VOLTAGE

**230**  
**460**

#### UPGRADE OPTIONS

**FP:** Fully Packaged  
Includes:  
- Aftercooler  
- Automatic Tank Drain  
- Installation Kit



- ✓ Built to last with premium parts
- ✓ Low RPM pump to decrease noise level
- ✓ Low cost of ownership
- ✓ 12-month warranty included
- ✓ 3-year extended warranty available
- ✓ Tank drain, ball valve, oil drain tube, and full synthetic oil included
- ✓ Large oil sight glass and liquid filled gauge included
- ✓ ETL Listed: Conforms to UL 1450 & CSA C22.2 NO. 68-92

#### UNIT SPECIFICATIONS

|                 |                                          |
|-----------------|------------------------------------------|
| HORSEPOWER      | 5                                        |
| TANK SIZE       | 60 Gallon                                |
| DIMENSIONS      | V: 30" x 21" x 73"<br>H: 52" x 23" x 47" |
| SHIPPING WEIGHT | 400 lbs.                                 |

#### PUMP SPECIFICATIONS

|                |                      |
|----------------|----------------------|
| STAGE          | 2                    |
| ACFM @ 175 PSI | 15                   |
| PUMP           | 2 Cylinder Cast Iron |
| PUMP RPM       | 755                  |
| MAIN BEARINGS  | 50,000 Hour          |
| OIL            | Full Synthetic       |

#### ELECTRICAL SPECIFICATIONS

| MOTOR RPM       |                   | 3450                |                 |     |     |  |
|-----------------|-------------------|---------------------|-----------------|-----|-----|--|
| PHASE/<br>VOLTS | FULL LOAD<br>AMPS | BREAKER<br>SIZE (A) | WIRE SIZE (AWG) |     |     |  |
|                 |                   |                     | 25'             | 50' | 75' |  |
| 1/230           | 20.3              | 35                  | 8               | 8   | 6   |  |
| 3/230           | 14.2              | 25                  | 10              | 10  | 8   |  |
| 3/460           | 6.4               | 15                  | 12              | 12  | 10  |  |

#### FULLY PACKAGED UPGRADE OPTION

- **OVERSIZED AFTERCOOLERS**
  - Remove over 60% of water vapor, humidity, or moisture.
- **ENERGY SAVING PNEUMATIC AUTOMATIC TANK DRAIN**
  - Drains condensate with zero air loss every time the compressor shuts off.
  - Prevents valves from fouling and reduces corrosion.
- **INCLUDES INSTALLATION KIT**
  - 4 mounting pads
  - 4 anchor bolts
  - 12" steel braided flex hose

#### SUITABLE FOR:



1-2 PERSON  
AUTO REPAIR  
SHOP



SERIOUS  
HOBBYIST



FARM

▼ NEXT SIZE DOWN:  
**A030V060**

▲ NEXT SIZE UP:  
**A050V080**

#### ACCESSORIES AVAILABLE



**Installation Kit**  
Part: Install-60V



**3-Year Extended Warranty Kit (V95)**  
Part: AX-V95



**Electronic Tank Drain Kit**  
Part: EL CRDV-177K



**1/2" x 12" Stainless Steel Flex Hose**  
Part: DT 1005 H



**1/2" x 30" Stainless Steel Flex Hose**  
Part: DT 3005 H



**Synthetic Compressor Oil**  
Part: LU 1082 GAL/LU 1082 QT

Single phase motor is not compatible with 208V.

A050V060.0