

FOUR WHEEL SERIES

311AX4, TC

MODEL	311AX4
Capacity*	3.0 GPM
Pressure*	1100 PSI
Pump	Triplex, Oil Bath, Direct Drive
Motor/Voltage**	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.
Coil (Steel Pipe) Cold Water Wrap, Spiral Heating Section	127' tall coil, Schedule 40
Burner, Pressure Atomizing, Auto Ignition, Fuel Consumption	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH
Fuel Tank	Plastic, 4.5 Gal.
Stack Size	8"
Temp. Control	Optional
Chemical	Low Pressure Injector
Float Tank	Plastic
Dimensions	L - 40" W - 27" H - 40"
Shipping Weight	420 lbs.



Note: All 115 volt units have ground fault interrupters standard.

*Gallonages and pressure may vary - + 5% due to manufacturing tolerances in components.

**Special voltages on request. Gallonages and pressure may be less on 3 phase current.

Also available ETL certified to UL 1776 standards and CSA-B140.11-M89.



Express Pressure Washers Inc.

526 3rd St NE

Blooming Prairie, MN 55917

PH: (507) 583-2703

www.expresspressurewashers.com